



itive control

free control

at the lever

Contents

	Page
Features	03
Functional description, section view	04
· Hydraulic operating diagram	04
Technical data	05
Ordering code	06
Control curves	07
Unit dimension	08-09

Features

1. Function:

- Precise linear control
- Perfect adjustment characteristic
- Easy and flexible operation

2. Applications



Horizontal directional
drilling



Tractor loader backhoes




Mining equipment




Drilling rigs

02



Technical data

Ordering code




Company code	– H –	
Number of control sections	*	For example: 3, means 3 sections
	blank	1 section
Structure type	2TH6	2 control channels
Actuator type	L	lever without detent
	P	lever held in any position by a friction coupling
	M	Three-points positioning (center position and neutral position on both sides)
	T	Three-point positioning + friction positioning
	F	Single-sided positioning (floating position)
	D	With electric button on lever upside
Control curve	97	control curve, NO. 97
	06	control curve, NO. 06
	70	control curve, NO. 70
	20	control curve, NO. 20
Standard installation and connection dimensions	1X	
Seals	M	NBR
	V	FKM
Connection threads	01	G1/4 pipe thread to standard ISO228/1




Unit dimensions

(dimensions in mm)




Unit dimensions

(dimensions in mm)



301.69



02

